



product description: elbows are intended for steel pipes without thread
both ends are fitted with sockets

material: steel

temperature resistance: -45 - +250 °C

mechanical resistance: 1250 N / 5 cm

classification according to EN 61386-1 ed. 2: 44561

mechanical protection according to EN 50102: IK10

meets the requirements: EN 61386-1 ed.2:09, EN 61386-21:04, EN 50102

storage: EN 60721-3-1

surface: ECZ - smooth steel material coated on both sides with black, medium corrosion resistance - group 2
F - hot dip galvanized, 45 µm (min. 35 µm), high corrosion resistance - group 4



item number	di min. inner Ø socket (mm)	R (mm)	weight 1 pc (kg)	package (pcs)	for pipes
6316E_ECZ	16	55	0,07	15	6216E_ECZ
6320_ECZ	20	70	0,11	25	6220_EOZ
6325_ECZ	25	115	0,21	25	6225_EOZ
6332_ECZ	32	125	0,28	20	6232_EOZ
6340_ECZ	40	140	0,48	15	6240_EOZ
6350_ECZ	50	170	0,69	5	6250_ECZ
6363_ECZ	63	210	1,20	3	6263_ECZ
6316E_ZN_F	16	55	0,07	15	6216E_ZN_F
6320_ZN_F	20	70	0,12	25	6220_ZN_F, 6220_ZNM_S
6325_ZN_F	25	115	0,22	25	6225_ZN_F, 6225_ZNM_S
6332_ZN_F	32	125	0,33	20	6232_ZN_F, 6232_ZNM_S
6340_ZN_F	40	140	0,52	15	6240_ZN_F, 6240_ZNM_S
6350_ZN_F	50	170	0,81	5	6250_ZN_F
6363_ZN_F	63	210	1,53	3	6263_ZN_F