



**product description:**

designed for distribution system with voltage 400 V and with maximum current 16 A  
 for premises with increased need for protection of persons and property  
 inlet openings made of flexible material  
 air-tightness even with inserted cable or pipe  
 suitable for low energy and passive houses  
 prevents airflow through the installation  
 mounting screws are fitted with a triple thread for quick installation  
 when mounting, it is not necessary to countersink the plasterboard edge  
 allows to install double-socket  
 after adjusting the edge possibly fitting multiple frames (spacing 71 mm)  
 possibility to insert a terminal plate and screwless terminals  
 when using box with the cover V 68HF, the IP protection is IP30

material: PP (halogen-free, Pb Free)

color: white

self-snuffing: yes, within 30 s

temperature resistance: -5 - +60 °C

flaming loop test: 850 °C

fire class for underlying material: A1-F

weight: 26 g

meets the requirements: ČSN EN 60670-1, ČSN EN IEC 60670-1 ed. 2:21

storage: ČSN 64 0090

**KU 68 LD/1HF\_HA - boxes fitted with screws for mounting into double wall and device screws; 90 pcs of boxes loose in carton**

accessories: cover V 68HF  
 terminal plate S-66  
 screwless terminal plates TYP015, TYP016, TYP017, TYP018

auxiliary tools: drill for hollow walls - set VDS 68 (universal carrier VPTU + saw-drill VPT 68)