

type number	A	for width of cable tray	thickness of metal sheet	max. load	weight
	mm	mm	mm	kg	kg/pc
NP 450_S	450	400	1,5	150	0,5
NP 550_S	550	500	1,5	150	0,62
NP 650_S	650	600	1,5	150	0,73
NP 450_ZM	450	400	1,5	150	0,5
NP 550_ZM	550	500	1,5	150	0,62
NP 650_ZM	650	600	1,5	150	0,73



product description:

The load bearing profile is intended as a support for the installation of cable ladders or trays. The load bearing profile is fixed by using two threaded rods ZT 10 + nut M 10 + washer PD 10.

The size of the load bearing profile is determined according to the width of the cable tray or cable ladder + 50 mm, for example for a cable tray that is 500 mm wide, order NP 550.

ZM surface finish load bearing profile shall be used for ZM or F surface finish trays.

These items can also be ordered in a varnished version.

surface finish:

S - Pre-Galvanized steel according to ČSN EN 10346, ČSN EN 10143, zinc-layer 15-27 µm

ZM - Pre-Galvanized steel with admixture of magnesium and aluminum according to ČSN EN 10346, ČSN EN 10143, protective layer 18-31 µm (replacement of hot dip galvanizing)

sales amount:

á 1 pc

meets the requirements: ČSN EN 61537:02

storage:

ČSN EN 60721-3-1

