

type number	screw diameter (mm)	screw length (mm)	sales amount (pcs)	
KVD 5X16_PO	5	16	200	🔥
KVD 5X20_PO	5	20	200	🔥
KVD 5X25_PO	5	25	200	🔥
KVD 5X30_PO	5	30	200	🔥
KVD 5X40_PO	5	40	100	🔥
KVD 5X50_PO	5	50	100	🔥
KVD 5X60_PO	5	60	100	🔥
KVD 5X70_PO	5	70	100	🔥



product description: Screw with fire functionality. Fire resistance E 30 - E 90. Ideal connection screw KVD_PO + clamp 67XX_PO.
The screws can also be used in chipboard and other materials.
The screw with full head protruding above the surface is fitted with a star groove TX20.

surface finish: Electrolytic galvanizing

classification 🔥: ČSN 73 0895 P 90-R
DIN 4102-12 E 90
STN 92 0205 PS 90
Fire classification depends on the specific conditions of the cable tray, detailed in the catalog Systems with maintained functionality in fire.

storage: ČSN EN 60721-3-1

⚠️ WARNING

Mechanical Injuries During Installation

Improper handling (e.g., tool slippage or insufficient fixation of the workpiece) may result in cuts, puncture wounds, or other mechanical injuries to fingers or hands.

Risk of Penetrating Electrical Installations

When installing screws into walls or structures that may contain electrical wiring, there is a risk of electric shock or short-circuiting. Always verify the presence of electrical or other utility lines before drilling or screwing into any surface.

recycling codes:



KVD