



## product description:

quick and safe installation without screws, installation only by pushing  
 terminals are intended for full Cu conductors  
 for wires with cross-section from 1,0-2,5 mm<sup>2</sup>  
 maximum working load of 24 A  
 for voltages of up to 450 V  
 transparent color for the visible control  
 color-coding stripe

| item number      | number of conductors | dimension (mm)    | color                                   |
|------------------|----------------------|-------------------|-----------------------------------------|
| <b>TYP017_XX</b> | 2                    | 10,5 x 9,5 x 19,3 | transparent + distinctive red stripe    |
| <b>TYP016_XX</b> | 3                    | 13,8 x 9,5 x 19,3 | transparent + distinctive orange stripe |
| <b>TYP018_XX</b> | 4                    | 17,6 x 9,5 x 19,3 | transparent + distinctive yellow stripe |
| <b>TYP015_XX</b> | 5                    | 21,1 x 9,5 x 19,3 | transparent + distinctive gray stripe   |

material: PC/PA 66

color: transparent + distinctive stripe

self-snuffing: yes, within 30 s

temperature resistance: -30 - +105 °C

meets the requirements: EN 60998-1; EN 60998-2-2

storage: ČSN 64 0090

## recycling symbols



terminal plate



cardboard

 **WARNING**

## risks associated with

using the products: incorrect electrical installation can cause a fire - we recommend the connection to be carried out exclusively by an authorized person  
 follow the manufacturer's installation instructions according to the installation instructions and videos  
 damage to the product - if the product is visibly damaged, stop using it  
 under normal and foreseeable conditions of use, the installed product does not pose any risks to consumers